

IP NETWORK CAMERA

IPMZB3MIR2812 & IPMZB3MIR832

You Talk, We Listen®
ONIX USA



Features

- Megapixel Recording
IPMZB3MIR2812
2.8-12mm, Up to 150ft IR
IPMZB3MIR832
8-32mm, Up to 300ft IR
- Outdoor Rated IP67
- EXIR Illuminators
- True Wide Dynamic Range
- IP67
- Audio & Alarm I/O
- SD Card – Up to 128GB
- ONVIF Compliant
- PoE

Part Number	IPMZB3MIR2812	IPMZB3MIR832
Resolution	2048 x 1536	
Frame Rate	15fps(2048x1536) 30fps(1920x1080) 30fps(1280x720)	
Image Sensor	1/3" Progressive Scan CMOS	
Lux Rating	0.001 Lux @ F1.4, 0 Lux with IR	
Shutter	1s ~ 1/100,000s	
Lens	2.8-12mm	8-32mm
DNR	3D DNR	
WDR	True Wide Dynamic Range	
Compression	H.264 / MJPEG	
H.264 Codec	Main Profile	
Bit Rate	32Kbps ~ 16Mbps	
Audio Compress	G.711 / G.726	
Audio Bit Rate	64Kbps (G.711) / 16Kbps (G.726)	
SD Recording	Mini SD Card: Up to 128GB	
Image Settings	Saturation, Brightness, Contrast, Sharpness	
BLC	Configurable by Zone	
Alarm Trigger	Motion, Alarm, Network Disconnect, IP Conflict, Storage Exception	
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos	
Interoperability	ONVIF, PSIA, CGI	
Security	User Authentication, Reset Button, Flickerless, Dual Stream, Heartbeat, Mirror, Watermark	
Communication	1-RJ45 10M / 100M Ethernet Interface	
Dimensions	105mm x 295.6mm (3.93" x 4.09" x 12.28")	
Weight	4.1lbs	
Operating Temp	-40 °F ~140 °F, Humidity 90% or less (non-condensing)	
Power Supply	AC24V 18W/Poe (802.3at)	
Power Consumpt	Max 18W	
Weather Rating	IP67	